


# Air Conditioning

## Product Information

### GUF-50RD4 : Lossnay Outdoor Air Processing Unit

R410A



The GUF-50RD4 Outdoor Air Processing Unit can be used with any of the extensive range of City Multi indoor units to provide ventilation, dust removal, humidification and heat recovery.

## FEATURES



### INDOOR

Heating Capacity (kW) (nominal)	6.21 (2.04)
Cooling Capacity (kW) (nominal)	5.57 (1.94)
High Performance Heating Capacity (kW) (UK)	6.42 (2.25)
COP Priority Heating Capacity (kW) (UK)	5.93 (2.08)
Cooling Capacity (kW) (UK)	5.03 (1.58)
Heating Power Input (kW) - Hi	0.265
Cooling Power Input (kW) - Hi	0.265
Airflow (m <sup>3</sup> /min) - Lo-Hi	6.67 - 8.33
External Static Pressure (Pa)	140
Sound Pressure Level (dBA) - Lo-Hi	29.5 - 34.5
Weight (kg)	54
Dimensions (mm) Width	1016
Dimensions (mm) Depth	1288
Dimensions (mm) Height	317
Electrical Supply	220-240V, 50HZ
Phase	SINGLE
Running Current (A) - Heating / Cooling - Hi	1.15 / 1.15
Fuse Rating (BS88) - HRC (A)	6
Mains Cable No. Cores	3

### DIMENSIONS

GUF-50RD4

