

Air Conditioning


Product Information

PEFY-P25VMS1-E : Indoor Unit

Ultra Thin Ceiling Concealed Ducted



The ultra thin ceiling concealed ducted indoor unit offers increased flexibility and is particularly suitable for places where low noise operation is desired from a slimline body.



FEATURES



INDOOR

Heating Capacity (kW) (nominal)	3.2
Cooling Capacity (kW) (nominal)	2.8
High Performance Heating Capacity (kW) (UK)	3.2
COP Priority Heating Capacity (kW) (UK)	3
Cooling Capacity (kW) (UK)	2.7
Cooling Capacity (Hi-Sens Mode) (kW) (UK)	2
SHF (UK)	0.78
SHF (Hi-Sens Mode) (UK)	0.9
Heating Power Input (kW) (nominal)	0.04
Cooling Power Input (kW) (nominal)	0.06
Airflow (m ³ /min) - Lo-Mi-Hi	5.5 - 7 - 9
External Static Pressure (Pa)	5 - 15 - 50
Sound Pressure Level (dBA) - Lo-Mi-Hi	24 - 26 - 30
Weight (kg)	19
Dimensions (mm) Width	790
Dimensions (mm) Depth	700
Dimensions (mm) Height	200
Electrical Supply	220-240V, 50HZ
Phase	SINGLE
Running Current (A) - Heating / Cooling	0.39 / 0.5
Fuse Rating (BS88) - HRC (A)	6
Mains Cable No. Cores	3

DIMENSIONS

PEFY-P25VMS1-E

