

# PLFY-P40VCM-E2

Indoor Unit

2x2 4-Way Blow Ceiling Cassette



The compact size of this unit is ideal for 600 by 600mm ceilings and with a depth of 208mm, this lightweight unit makes installation a breeze. This unit also comes complete with a long life filter that will last for approximately 2,500 hours.

- Compact size for handy installation and easy maintenance
- Only 208mm high
- Fresh air duct facility




Pictures not to scale

### **Product Details**


PLFY-P40VCM-E2	
Capacity (kW):	
Heating (Nominal)	5.0
Cooling (Nominal)	4.5
Heating (UK)	5.0
Cooling (UK)	4.3
R410A High Sensible Cooling (UK)	3.3
SHF R410A (UK)	0.7
SHF High Sensible R410A (UK)	0.76
Power Input (kW) Heating (Nominal)	0.06
Power Input (kW) Cooling (Nominal)	0.06
Airflow(m3/min)(Heating /Cooling) - Lo-Mi-Hi	8-9-11 /8-9-11
Noise (dBA) (Heating/Cooling) - Lo-Mi-Hi	30-34-3930-34-39
Noise (dBA) (Heating/Cooling) - Lo-Mi-Hi Width (grille) - mm	30-34-3930-34-39 570 (650)
· / · · · · · · · · · · · · · · · · · ·	
Width (grille) - mm	570 (650)
Width (grille) - mm  Depth (grille) - mm	570 (650) 570 (650)
Width (grille) - mm  Depth (grille) - mm  Height (grille) - mm	570 (650) 570 (650) 235 (255)
Width (grille) - mm  Depth (grille) - mm  Height (grille) - mm  Weight (grille) - kg	570 (650) 570 (650) 235 (255) 17 (20)
Width (grille) - mm  Depth (grille) - mm  Height (grille) - mm  Weight (grille) - kg  Electrical Supply	570 (650) 570 (650) 235 (255) 17 (20) 220-240v, 50Hz
Width (grille) - mm  Depth (grille) - mm  Height (grille) - mm  Weight (grille) - kg  Electrical Supply  Phase	570 (650) 570 (650) 235 (255) 17 (20) 220-240v, 50Hz Single
Width (grille) - mm  Depth (grille) - mm  Height (grille) - mm  Weight (grille) - kg  Electrical Supply  Phase  Mains Cable No. Cores	570 (650) 570 (650) 235 (255) 17 (20) 220-240v, 50Hz Single

#### Dimension

## PLFY-P40VCM-E2



## Side View >





Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.





