Air Conditioning

Product Information PLFY-P125VLMD-E : Indoor Unit 2-Way Blow Ceiling Cassette





The PLFY-P-VLMD-E cassette unit fits into the space in a suspended ceiling to provide heating or cooling. This new unit has been redesigned with lower unit height and lower noise levels.



FEATURES



Mains Cable No. Cores

Grille Model Reference







3

CMP-125VLW-C

















| INDOOR | |
|---|----------------|
| Heating Capacity (kW) (nominal) | 16 |
| Cooling Capacity (kW) (nominal) | 14 |
| High Performance Heating Capacity (kW) (UK) | 16 |
| COP Priority Heating Capacity (kW) (UK) | 15 |
| Cooling Capacity (kW) (UK) | 13.3 |
| Cooling Capacity (Hi-Sens Mode) (kW) (UK) | 10.2 |
| SHF (UK) | 0.73 |
| SHF (Hi-Sens Mode) (UK) | 0.8 |
| Heating Power Input (kW) (nominal) | 0.27 |
| Cooling Power Input (kW) (nominal) | 0.28 |
| Airflow (m³/min) - Lo-Mi-Hi | 24 - 27 - 33 |
| Sound Pressure Level (dBA) - Lo-Mi-Hi | 40 - 42 - 46 |
| Weight (kg) (Grille) | 56 (13) |
| Dimensions (mm) Width (Grille) | 1708 (2010) |
| Dimensions (mm) Depth (Grille) | 606 (710) |
| Dimensions (mm) Height (Grille) | 290 (20) |
| Electrical Supply | 220-240V, 50HZ |
| Phase | SINGLE |
| Running Current (A) - Heating / Cooling | 1.33 / 1.35 |
| Fuse Rating (BS88) - HRC (A) | 6 |

DIMENSIONS

PLFY-P125VLMD-E







Side View >

Lower View >



MITSUBISHI ELECTRIC LIVING ENVIRONMENTAL SYSTEMS

Telephone: 01707 282880 Fax: 01707 278881 Email: airconditioning@meuk.mee.com Website: http://www.airconditioning.mitsubishielectric.co.uk

Country of origin: United Kingdom – Japan – Thailand – Malaysia. (D) Mitsubishi Electric Europe 2013. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks of their respective owners.