


PQHY-P500YSGM-A

WY Series 20hp Water Cooled Condensing Unit R410A Heat Pump



- High COP's possible thanks to increased efficiency and careful control of the system, allowing the largest operational water circuit temperature band ever
- Combining WY with waste heat energy provides unique application solutions
- Condensing units can be situated indoors allowing greater design flexibility and no limitation on building size
- Single inverter compressor
- Improved pipe run of 150m with a total system pipe length of up to 300m
- High Sensible Cooling Function By raising the off coil temperature, a 10% increase in sensible cooling capacity over standard operation is achievable, the result being greater comfort for occupants
- Now able to operate with closed loop ground source water temperatures, bore hole and slinky applications are now possible





Pictures not to scale


Product Details

PQHY-P500YSGM-A	
Capacity (kW):	
Heating (Nominal)	63.0
Cooling (Nominal)	56.0
Power Input (kW) Heating (Nominal)	13.6
Power Input (kW) Cooling (Nominal)	15.06
Max No. of Connectable Indoor Units	24
Noise (dBA)	53
Width - mm	1980
Depth - mm	550
Height - mm	1800
Weight - kg	208 + 248
Electrical Supply	380-415v, 50Hz
Phase	3
Mains Cable No. Cores	4 +earth
Starting Current (A)	8
Running Current (A) - Heating	21
Running Current (A) - Cooling	23.3
Fuse Rating (BS88) - HRC (A)	50

Piping Restrictions	
Total Piping Length (m)	300
Furthest Piping Length (m)	150
Furthest Piping Length after 1st Branch (m)	40
Between Indoor and Outdoor Units - Height (m)	50
Between Indoor and Indoor Units - Height (m)	15

Dimension

PQHY-P500YSGM-A





Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.





