

PQHY-P400YSHM-A

WY Series 16hp Water Cooled Condensing Unit

R410A Heat Pump





Pictures not to scale


Product Details

PQHY-P400YSHM-A	
Capacity (kW):	
Heating (Nominal)	50.0
Cooling (Nominal)	45.0
Power Input (kW) Heating (Nominal)	8.65
Power Input (kW) Cooling (Nominal)	8.25
Max No. of Connectable Indoor Units	40
Noise (dBA)	50
Width - mm	880 + 880
Depth - mm	550
Height - mm	1160
Weight - kg	186 + 186
Electrical Supply	380- 415v, 50Hz
Phase	3
Mains Cable No. Cores	4 + earth
Starting Current (A)	8
Running Current (A) - Heating	13.3
Running Current (A) - Cooling	12.7

Piping Restrictions	
Total Piping Length (m)	500
Furthest Piping Length (m)	165
Between Outdoor and BC Controller - Length (m)	40
Between Indoor and Outdoor Units - Height (m)	50
Between Indoor and Indoor Units - Height (m)	15

imensions

PQHY-P400YSHM-A





Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

CE

Modaliter

Air C

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.

