Air Conditioning

Product Information

PQHY-P800YSHM-A: WY Series 32hp Water

Cooled Unit

R410A Heat Pump





The WY Series has all the benefits of the Y Series using water cooled condensing units. It is also able to produce heat recovery via the water circuit between heat source units, making for a very economical system. Like the air source versions, the water cooled units benefit from a modular design approach. A twinning kit is required for double combinations.



FEATURES











DIMENSIONSPQHY-P800YSHM-A

Upper View >

OUTDOOR		
Heating Capacity (kW) (nominal)	100	
Cooling Capacity (kW) (nominal)	90	
Heating Power Input (kW) (nominal)	20.74	
Cooling Power Input (kW) (nominal)	19.18	
COP / EER (nominal)	4.82 / 4.69	
SCOP / SEER	4.85 / 5.89	
Max No. of Connectable Indoor Units	50	
Sound Pressure Level (dBA)	54	
Sound Power Level (dBA)	68	
Weight (kg)	195 + 195 + 195	
Dimensions (mm) Width x Depth x Height	880 + 880 + 880 x 550 x 1160	
Electrical Supply	380-415V, 50HZ	
Phase	3	
Starting Current (A)	8/8/8	
Running Current (A) - Heating	32	
Running Current (A) - Cooling	29.6	
Fuse Rating (BS88) - HRC (A)	20/20/20	
Mains Cable No. Cores	4 + EARTH	

	1160
-	5V, 50HZ
	3
	8/8/8
	32
	29.6
	0/20/20
L	+ EARTH
	500
	165
	40
	50

PIPING RESTRICTIONS	
Total Piping Length (m)	500
Furthest Piping Length (m)	165
Furthest Piping Length After First Branch (m)	40
Between Indoor and Outdoor units - Height (m)	50
Between Indoor and Indoor units - Height (m)	15



