

PQRY-P250YGM-A

WR2 Series 10hp Water Cooled Condensing Unit R410A Heat Recovery



Simultaneous Heating and Cooling with Double Heat Recovery

The WR2 Series has double heat recovery potential, making this system very economical. Not only does it produce heat recovery from the indoor units on the same 2-pipe refrigerant circuit, it also produces heat recovery via the water circuit between heat source units. This series has all the benefits of the R2 Series with water cooled condensing units, using a single inverter compressor.

- High COP's possible thanks to increased efficiency and careful control of the system, allowing the largest operational water circuit temperature band ever
- Total building heat recovery made possible by exchanging energy in both refrigerant and water circuits
- Combining WR2 with waste heat energy provides unique application solutions
- Condensing units can be situated indoors allowing greater design flexibility and no limitation on building size
- Improved pipe run of 150m with a total system pipe length of up to 400m
- High Sensible Cooling Function By raising the off coil temperature, a 10% increase in sensible cooling capacity over standard operation is achievable, the result being greater comfort for occupants
- Now able to operate with closed loop ground source water temperatures, bore hole and slinky applications are now possible



Pictures not to scale


Product Details

PQRY-P250YGM-A	
Capacity (kW):	
Heating (Nominal)	31.5
Cooling (Nominal)	28.0
Power Input (kW) Heating (Nominal)	5.8
Power Input (kW) Cooling (Nominal)	5.95
Max No. of Connectable Indoor Units	19
Noise (dBA)	47
Width - mm	990
Depth - mm	550
Height - mm	1800
Weight - kg	266
Electrical Supply	380-415v, 50Hz
Phase	3
Mains Cable No. Cores	4 + earth
Starting Current (A)	8
Running Current (A) - Heating	8.9
Running Current (A) - Cooling	9.1
Fuse Rating (BS88) - HRC (A)	25

Piping Restrictions	
Total Piping Length (m)	400
Furthest Piping Length (m)	150
Between Outdoor and BC Controller (Master) - Length (m)	110
Length Between Indoor and BC Controller (Master / Slave) - Length (m)	60
Between Indoor and Outdoor Units - Height (m)	50
Between Indoor and Indoor Units - Height (m)	15
Between Indoor and BC Controller (Master/Slave) - Height (m)	15
Between Indoor (Master) and Indoor (Slave) - Height (m)	15

Dimension

PQRY-P250YGM-A





Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.





