

# Air Conditioning

## Product Information

**PUHY-RP200YJM-B : Replace Multi Y Series**

**8hp Outdoor Unit**

R410A Heat Pump



The latest VRF Replace Multi from Mitsubishi Electric is specifically designed for the maturing refurbishment sector, enabling the reuse of existing R22/R407c pipework, whilst also allowing the upgrade to some of the most efficient systems available in the market.

## FEATURES



### OUTDOOR

Heating Capacity (kW) (nominal)	25
Cooling Capacity (kW) (nominal)	22.4
High Performance Heating Capacity (kW) (UK)	25
COP Priority Heating Capacity (kW) (UK)	22.8
Cooling Capacity (kW) (UK)	19.9
Heating Power Input (kW) (nominal)	5.69
Cooling Power Input (kW) (nominal)	5.68
High Performance Heating Power Input (kW) (UK)	7.34
COP Priority Heating Power Input (kW) (UK)	5.63
Cooling Power Input (kW) (UK)	4.43
COP / EER (nominal)	4.39 / 3.94
SCOP / SEER	- / 6.42
Max No. of Connectable Indoor Units	17
Airflow (m <sup>3</sup> /min)	185
Sound Pressure Level (dBA)	56
Sound Power Level (dBA)	76
Weight (kg)	230
Dimensions (mm) Width x Depth x Height	920 x 760 x 1710
Electrical Supply	380-415V, 50HZ
Phase	3
Starting Current (A)	8
Running Current (A) - Heating	8.7
Running Current (A) - Cooling	8.7
Fuse Rating (MCB sizes BS EN 60947-2) - (A)	20
Mains Cable No. Cores	4 + EARTH

### PIPING RESTRICTIONS

Total Piping Length (m)	300
Furthest Piping Length (m)	120
Furthest Piping Length After First Branch (m)	40
Between Indoor and Outdoor units - Height (m)	50
Between Indoor and Indoor units - Height (m)	15

### DIMENSIONS

PUHY-RP200YJM-B

