

## PUMY-P140VHM

Y Series 6hp Outdoor Unit

R410A Heat Pump

The latest in Mitsubishi Electric Y Series technology incorporated within the new City Multi 6hp model allows up to 8 indoor units to be connected to a single outdoor unit, using the standard branch/header pipework system proven in 8 & 10hp models. Utilising the latest Mitsubishi Electric Inverter technology, the system is fully controllable with all City Multi controllers or linked to third party BEMS.

- A two core non-polar transmission line allows for simple installation of up to 8 indoor units
- The condensing unit is extremely slimline which allows easy location and application of the system





Pictures not to scale



PUMY-P140VHM	
Capacity (kW):	
Heating (Nominal)	18.0
Cooling (Nominal)	15.5
Heating (UK)	14.9
Cooling (UK)	14.3
Power Input (kW) Heating (Nominal)	5.58
Power Input (kW) Cooling (Nominal)	5.35
Power Input (kW) Heating (UK)	4.99
Power Input (kW) Cooling (UK)	4.53
Max No. of Connectable Indoor Units	8
Airflow (m3/min) (Heating / Cooling)	100 / 100
Noise (dBA) (Heating/ Cooling)	5351
Pipe Size Gas mm (in)	15.88 (5/8)
Pipe Size Liquid mm (in)	9.52 (3/8)
Width - mm	950
Depth - mm	330 + 30
Height - mm	1350
Weight - kg	127
Electrical Supply	220-240v, 50Hz
Phase	Single
Mains Cable No. Cores	3
Starting Current (A)	5
Running Current (A) - Heating	23.6
Running Current (A) - Cooling	22.7
Fuse Rating (BS88) - HRC (A)	50

PUMY-P140VHM







Piping Restrictions	
Total Piping Length (m)	120
Furthest Piping Length (m)	80
Furthest Piping Length after 1st Branch (m)	30
Between Indoor and Outdoor Units - Height (m)	30
Between Indoor and Indoor Units - Height (m)	12



## Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.



