

PUMY-P125VHMA

Y Series 5hp Outdoor Unit

R410A Heat Pump



- A two core non-polar transmission line allows for simple installation of up to 8 indoor units
- The condensing unit is extremely slimline which allows easy location and application of the system



Pictures not to scale




Product Details


| PUMY-P125VHMA | |
|-------------------------------------|----------------|
| Capacity (kW): | |
| Heating (Nominal) | 16.0 |
| Cooling (Nominal) | 14.0 |
| Heating (UK) | 13.3 |
| Cooling (UK) | 12.9 |
| Power Input (kW) Heating (Nominal) | 4.33 |
| Power Input (kW) Cooling (Nominal) | 4.32 |
| Power Input (kW) Heating (UK) | 3.85 |
| Power Input (kW) Cooling (UK) | 3.66 |
| Max No. of Connectable Indoor Units | 8 |
| Airflow(m3/min)(Heating /Cooling) | 100 /100 |
| Noise (dBA) (Heating/Cooling) | 5250 |
| Pipe Size Gas mm (in) | 15.88 (5/8) |
| Pipe Size Liquid mm (in) | 9.52 (3/8) |
| Width - mm | 950 |
| Depth - mm | 330+30 |
| Height - mm | 1350 |
| Weight - kg | 127 |
| Electrical Supply | 220-240v, 50Hz |
| Phase | Single |
| Mains Cable No. Cores | 3 |
| Starting Current (A) | 5 |
| Running Current (A) - Heating | 18.3 |
| Running Current (A) - Cooling | 18.3 |
| Fuse Rating (BS88) - HRC (A) | 40 |

| Piping Restrictions | |
|---|-----|
| Total Piping Length (m) | 120 |
| Furthest Piping Length (m) | 80 |
| Furthest Piping Length after 1st Branch (m) | 30 |
| Between Indoor and Outdoor Units - Height (m) | 30 |
| Between Indoor and Indoor Units - Height (m) | 12 |

Dimension

PUMY-P125VHMA







Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.



Tel:

Fax:



