Product Information

PUMY-P100VHMB: Y Series 4hp Outdoor

Unit

R410A Heat Pump

Air Conditioning





The latest in Mitsubishi Electric Y Series technology incorporated within the new City Multi 4hp model allows up to 8 indoor units to be connected to a single outdoor unit, using the standard branch/header pipework system proven in the larger models. Utilising the latest Mitsubishi Electric Inverter technology, the system is fully controllable with all City Multi controllers or linked to third party BEMS.



FEATURES









OUTDOOR	
Heating Capacity (kW) (nominal)	12.5
Cooling Capacity (kW) (nominal)	11.2
Heating Capacity (kW) (UK)	10.4
Cooling Capacity (kW) (UK)	10.3
Heating Power Input (kW) (nominal)	3.66
Cooling Power Input (kW) (nominal)	3.34
Heating Power Input (kW) (UK)	3.27
Cooling Power Input (kW) (UK)	2.84
COP / EER (nominal)	3.42 / 3.35
SCOP / SEER	3.5 / 5.5
Energy Efficiency Class - Heating / Cooling	A/A
Max No. of Connectable Indoor Units	8
Max Connectable Capacity	130%
Airflow (m³/min)	100
Pipe Size Gas (mm [in])	15.88 (5/8)
Pipe Size Liquid (mm ([in])	9.52 (3/8)
Sound Pressure Level (dBA)	49
Sound Power Level (dBA) Cooling	70
Weight (kg)	129
Dimensions (mm) Width x Depth x Height	950 x 330+30 x 1350
Electrical Supply	220- 240V, 50HZ
Phase	SINGLE
Starting Current (A)	5
Running Current (A) - Heating	15.5
Running Current (A) - Cooling	14.1
Guaranteed Operating Range (°C) - Heating	-15 ~ 15
Guaranteed Operating Range (°C) - Cooling	-5 ~ 46
Fuse Rating (BS88) - HRC (A)	32
Mains Cable No. Cores	3
PIPING RESTRICTIONS	
Total Piping Length (m)	120
Furthest Piping Length (m)	80
Furthest Piping Length After First Branch (m)	30
Between Indoor and Outdoor units - Height (m)	50
Between Indoor and Indoor units - Height (m)	12

DIMENSIONS

PUMY-P100VHMB





