

Air Conditioning

Product Information

PUMY-P R410A
Inverter Heat Pump (12.5-22.4kW)
Multi-Split Units

Making a
World of
Difference

Multi-Splits



The **PUMY Series** allow up to 10 indoor units to be connected to a single outdoor unit, using the standard City Multi branch pipework system or via branch boxes and/or LEV kits to connect M Series or Mr Slim indoor units. This makes it an economic and efficient answer for multi-room applications, whilst also offering space saving benefits.

Key Features

- The condensing unit is extremely slimline which allows easy location and application of the system
- Connect stylish M Series wall mounted and floor mounted indoor units to the system via the LEV kit interface (PAC-LV11M)
- Connect M Series and Mr Slim indoor units via the PAC-MK-BC boxes alongside VRF indoor units to the same system



Cooling | Heating | Ventilation | Controls

Air Conditioning

Product Information

PUMY-P R410A Inverter Heat Pump (12.5-22.4kW) Multi-Split Units

Making a
World of
Difference




PUMY-P OUTDOOR UNITS		PUMY-P112VKM3	PUMY-P112YKM3	PUMY-P125VKM3	PUMY-P125YKM3	PUMY-P140VKM3	PUMY-P140YKM3	PUMY-P200YKM1
NUMBER OF CONNECTABLE INDOOR UNITS	Branch box / Mixed*1	8 / 10	8 / 10	8 / 10	8 / 10	8 / 10	8 / 10	8 / 10
CAPACITY (kW)	Heating (nominal)	14.0	14.0	16.0	16.0	18.0	18.0	25.0
	Cooling (nominal)	12.5	12.5	14.0	14.0	15.5	15.5	22.4
	Heating (UK)	11.6	11.6	13.3	13.3	14.9	14.9	25.0
	Cooling (UK)	11.5	11.5	12.9	12.9	14.3	14.3	18.5
COP / EER (NOMINAL)		4.61 / 4.48	4.61 / 4.48	4.28 / 4.05	4.28 / 4.05	4.03 / 3.43	4.03 / 3.43	4.28 / 3.70
SCOP / SEER		3.93 / 6.45	3.93 / 6.45	4.16 / 6.52	4.16 / 6.52	3.79 / 6.33	3.79 / 6.33	3.83 / 5.99
MAX AIRFLOW (m³/min)	Heating / Cooling	110	110	110	110	110	110	139
SOUND PRESSURE LEVEL (dBA)		49	49	50	50	51	51	56
SOUND POWER LEVEL (dBA)	Cooling	69	69	70	70	71	71	76
DIMENSIONS (mm)	Width x Depth x Height	1050 x 330+25 x 1338	1050 x 330+25 x 1338	1050 x 330+25 x 1338	1050 x 330+25 x 1338	1050 x 330+25 x 1338	1050 x 330+25 x 1338	1050 x 330+25 x 1338
WEIGHT (kg)		122	125	122	125	122	125	137
ELECTRICAL SUPPLY		220-240v, 50Hz	380-415v, 50Hz	220-240v, 50Hz	380-415v, 50Hz	220-240v, 50Hz	380-415v, 50Hz	380-415v, 50Hz
PHASE		Single	Three	Single	Three	Single	Three	Three
POWER INPUT (kW)	Heating/Cooling (nominal)	3.04 / 2.79	3.04 / 2.79	3.74 / 3.46	3.74 / 3.46	4.47 / 4.52	4.47 / 4.52	5.84 / 6.05
	Heating/Cooling (UK)	2.71 / 1.87	2.71 / 1.87	3.33 / 2.32	3.33 / 2.32	3.98 / 3.03	3.98 / 3.03	7.59 / 5.58
STARTING CURRENT (A)		14	7	14	7	14	7	7
RUNNING CURRENT (A)	Heating/Cooling [MAX]	12.86 / 11.80 [29.5]	4.98 / 4.57 [13.0]	15.82 / 14.64 [29.5]	5.78 / 5.35 [13.0]	18.91 / 19.12 [29.5]	6.55 / 6.62 [13.0]	8.74 / 9.05 [19.0]
FUSE RATING (BS88) - HRC (A)		1 x 32	1 x 16	1 x 32	1 x 16	1 x 32	1 x 16	1 x 20
PIPE SIZE MM (in)	Gas	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	19.05 (3/4")
	Liquid	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8") ²
TOTAL PIPING LENGTH (m)	Branch box / Mixed*1	150 / 300 (240)	150 / 300 (240)	150 / 300 (240)	150 / 300 (240)	150 / 300 (240)	150 / 300 (240)	150 / 150 (150)
FURTHEST PIPING LENGTH (m)	(With no branch boxes)	80 (85)	80 (85)	80 (85)	80 (85)	80 (85)	80 (85)	80
BETWEEN BRANCH BOX AND OUTDOOR UNIT - LENGTH (m)		55	55	55	55	55	55	55
BETWEEN BRANCH BOX AND INDOOR UNIT - LENGTH (m)		25	25	25	25	25	25	25
BETWEEN INDOOR AND OUTDOOR UNIT - HEIGHT (m)		50m max ³	50m max ³	50m max ³	50m max ³	50m max ³	50m max ³	50m max ³
BETWEEN INDOOR AND INDOOR UNITS - HEIGHT (m)	Branch box / Mixed*1	12	12	12	12	12	12	12
CHARGE REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) - R410A (GWP 2088)		4.8 / 10.0	4.8 / 10.0	4.8 / 10.0	4.8 / 10.0	4.8 / 10.0	4.8 / 10.0	7.3 / 15.2
MAX ADDITIONAL REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) - R410A (GWP 2088)		13.7 / 28.6	13.7 / 28.6	13.7 / 28.6	13.7 / 28.6	13.7 / 28.6	13.7 / 28.6	13.5 / 28.2

Notes: *1 Branch box - only using branch boxes (PAC-MK) on the system. **Mixed** - using a mix of branch boxes (PAC-MK) and City Multi indoor units on the same system. Figure in brackets - when using 2 branch boxes.
² 12.7mm (1/2") if furthest length ≥ 60m. ³ 40m max if outdoor installed below.


PAC-MK - BRANCH BOX	PAC-MK31BC	PAC-MK51BC	PAC-LV - LEV KIT INTERFACE	PAC-LV11M	
NUMBER OF CONNECTABLE INDOOR UNITS	3	5	NUMBER OF CONNECTABLE INDOOR UNITS	1	
COMPATIBLE INDOOR UNITS	M Series, Mr Slim	M Series, Mr Slim	COMPATIBLE INDOOR UNITS	M Series	
WEIGHT (kg)	6.7	7.4	CAPACITY INDEX OF INDOOR UNITS	15 to 50	
DIMENSIONS (mm)	Width x Depth x Height	450 x 280 x 170	450 x 280 x 170	WEIGHT (kg)	3.5
POWER SUPPLY TO	From outdoor unit	3 core + earth	3 core + earth	DIMENSIONS (mm)	Width x Depth x Height
BRANCH BOX*1	Separate supply	220-240v, 50Hz / Single Phase	220-240v, 50Hz / Single Phase	ELECTRICAL SUPPLY	220-240v, 50Hz / Single Phase
	Separate supply fuse rating (BS88) - HRC (A)	6	6	FUSE RATING (BS88) - HRC (A)	6
POWER SUPPLY TO INDOOR UNITS	From branch box	3 core + earth	3 core + earth		

PRODUCT DIMENSIONS


Upper View




Rear View




Side View



Front View



Side View



Telephone: 01707 282880
 email: airconditioning@meuk.mee.com
 web: airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division
 Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland
 Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom - Japan - Thailand - Malaysia. ©Mitsubishi Electric Europe 2017. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

Note: The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Mitsubishi Electric's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R410A (GWP:2088), R32 (GWP:675), R407C (GWP:1774) or R134a (GWP:1430). *These GWP values are based on Regulation (EU) No 517/2014 from IPCC 4th edition. In case of Regulation (EU) No.626/2011 from IPCC 3rd edition, these are as follows: R410A (GWP:1975), R32 (GWP: 550), R407C (GWP:1650) or R134a (GWP:1300).



www.greengateway.mitsubishielectric.co.uk
 Mitsubishi Electric UK's commitment to the environment

Follow us @meuk_Jes
 Follow us @green_gateway

Mitsubishi Electric
 Living Environmental Systems UK

mitsubishielectric2

thehub.mitsubishielectric.co.uk

Effective as of September 2017