

Air Conditioning

Product Information

LGH-50RSDC-E1 : DC LOSSNAY

Residential Series



Particularly suitable for modern homes with high insulation afforded by double glazing and cavity insulation, which require ventilation to remove stale air without major heat loss. This model is also suitable for a number of non-residential applications such as schools

FEATURES



LOSSNAY

Airflow (m ³ /h) - Fan Speed 5-4-3-2-1	90-144-215-305-395
External Static Pressure (Pa) - Fan Speed 5-4-3-2-1	7-15-30-60-100
Sounds Pressure Level (dBA) - Ventilation Mode - Fan Speed 5-4-3-2-1	18-18-21-26.5-31
Sounds Pressure Level (dBA) - Bypass Mode - Fan Speed 5-4-3-2-1	18-18-21-26.5-31
Electrical Supply	220-240V, 50HZ
Fuse Rating (BS88) - HRC (A)	6
Starting Current (A)	2.5
Power Input (W) - Fan Speed 5-4-3-2-1	14-22-41-90-165
Temperature Exchange Efficiency (%) - Fan Speed 5-4-3-2-1	90-88-85.5-81.5-77.5
Enthalpy Exchange Efficiency Heating (%) - Fan Speed 5-4-3-2-1	84-82-79-75-71
Enthalpy Exchange Efficiency Cooling (%) - Fan Speed 5-4-3-2-1	83-80.5-77-72.5-68
Dimensions (mm) - W-D-H	1099+73-898-302
Weight (kg)	48
Duct Size (mm)	200

DIMENSIONS

LGH-50RSDC-E1

