

Air Conditioning

Product Information

LGH-150RX5-E : LOSSNAY

Commercial Series



This commercially orientated system can be utilised virtually anywhere to extract stale air and then recover the heating or cooling energy to either warm or cool incoming fresh air.

FEATURES



Airflow (m ³ /h) - Lo-Hi-ExHi	1300-1500-1500
External Static Pressure (Pa) - Lo-Hi-ExHi	100-135-175
Sound Pressure Level (dBA) Lossnay Ventilation - Lo-Hi-ExHi	35-37.5-39
Sound Pressure Level (dBA) Bypass Ventilation - Lo-Hi-ExHi	37-39-40.5
Electrical Supply	220-240V, 50HZ
Fuse rating (BS88) - HRC (A)	10
Starting Current (A)	7.3
Running Current (A) - Lo-Hi-ExHi	2.90-3.20-3.50
Power Input (W) - Lo-Hi-ExHi	680-740-830
Temperature Exchange Efficiency (%) - Lo-Hi-ExHi	81-80-80
Enthalpy Exchange Efficiency Heating (%) - Lo-Hi-ExHi	72.5-72-72
Enthalpy Exchange Efficiency Cooling (%) - Lo-Hi-ExHi	71.5-70.5-70.5
Dimensions (mm) - W-D-H	1004-1144-798
Weight (kg)	105
Duct Size (mm)	(SA,RA)250 (OA,EA)270X700

DIMENSIONS

LGH-150RX5-E

