

# Air Conditioning

## Product Information

**LGH-25RX5-E : LOSSNAY**

Commercial Series



This commercially orientated system can be utilised virtually anywhere to extract stale air and then recover the heating or cooling energy to either warm or cool incoming fresh air.



## FEATURES



### LOSSNAY

Airflow (m <sup>3</sup> /h) - ExLo-Lo-Hi-ExHi	105-155-250-250
External Static Pressure (Pa) - ExLo-Lo-Hi-ExHi	9-25-60-85
Sound Pressure Level (dBA) Lossnay Ventilation - ExLo-Lo-Hi-ExHi	19-21.5-26-27
Sound Pressure Level (dBA) Bypass Ventilation - ExLo-Lo-Hi-ExHi	19-22-26.5-27.5
Electrical Supply	220-240V, 50HZ
Fuse Rating (BS88) - HRC (A)	6
Starting Current (A)	0.9
Running Current (A) - ExLo-Lo-Hi-ExHi	0.18-0.27-0.48-0.55
Power Input (W) - ExLo-Lo-Hi-ExHi	42-62-114-129
Temperature Exchange Efficiency (%) - ExLo-Lo-Hi-ExHi	83.5-81.5-79-79
Enthalpy Exchange Efficiency Heating (%) - ExLo-Lo-Hi-ExHi	77.5-74-69.5-69.5
Enthalpy Exchange Efficiency Cooling (%) - ExLo-Lo-Hi-ExHi	76-72.5-68-68
Dimensions (mm) - W-D-H	735-780-273
Weight (kg)	20
Duct Size (mm)	150

### DIMENSIONS

LGH-25RX5-E

