

Air Conditioning

Product Information

LGH-35RX5-E : LOSSNAY

Commercial Series



This commercially orientated system can be utilised virtually anywhere to extract stale air and then recover the heating or cooling energy to either warm or cool incoming fresh air.

FEATURES



LOSSNAY

Airflow (m ³ /h) - ExLo-Lo-Hi-ExHi	115-210-350-350
External Static Pressure (Pa) - ExLo-Lo-Hi-ExHi	9-30-80-160
Sound Pressure Level (dBA) Lossnay Ventilation - ExLo-Lo-Hi-ExHi	18-23-29.5-32
Sound Pressure Level (dBA) Bypass Ventilation - ExLo-Lo-Hi-ExHi	18-24-30.5-32.5
Electrical Supply	220-240V, 50HZ
Fuse Rating (BS88) - HRC (A)	6
Starting Current (A)	2.4
Running Current (A) - ExLo-Lo-Hi-ExHi	0.30-0.51-0.74-0.92
Power Input (W) - ExLo-Lo-Hi-ExHi	69-116-169-212
Temperature Exchange Efficiency (%) - ExLo-Lo-Hi-ExHi	88-85-80-80
Enthalpy Exchange Efficiency Heating (%) - ExLo-Lo-Hi-ExHi	81.5-76.5-71.5-71.5
Enthalpy Exchange Efficiency Cooling (%) - ExLo-Lo-Hi-ExHi	81-75.5-71-71
Dimensions (mm) - W-D-H	874-888-315
Weight (kg)	29
Duct Size (mm)	150

DIMENSIONS

LGH-35RX5-E

