

# Air Conditioning

## Product Information

**LGH-100RX5-E : LOSSNAY**

Commercial Series



This commercially orientated system can be utilised virtually anywhere to extract stale air and then recover the heating or cooling energy to either warm or cool incoming fresh air.



## FEATURES



### LOSSNAY

Airflow (m <sup>3</sup> /h) - ExLo-Lo-Hi-ExHi	415-755-1000-1000
External Static Pressure (Pa) - ExLo-Lo-Hi-ExHi	18-60-110-170
Sound Pressure Level (dBA) Lossnay Ventilation - ExLo-Lo-Hi-ExHi	22-32.5-35-37
Sound Pressure Level (dBA) Bypass Ventilation - ExLo-Lo-Hi-ExHi	22-33-36-38
Electrical Supply	220-240V, 50HZ
Fuse Rating (BS88) - HRC (A)	6
Starting Current (A)	4.6
Running Current (A) - ExLo-Lo-Hi-ExHi	0.90-1.70-2.10-2.40
Power Input (W) - ExLo-Lo-Hi-ExHi	200-380-475-535
Temperature Exchange Efficiency (%) - ExLo-Lo-Hi-ExHi	87-83-80-80
Enthalpy Exchange Efficiency Heating (%) - ExLo-Lo-Hi-ExHi	80-74-?-?
Enthalpy Exchange Efficiency Cooling (%) - ExLo-Lo-Hi-ExHi	79-73-71-?
Dimensions (mm) - W-D-H	1231-1144-399
Weight (kg)	59
Duct Size (mm)	250

### DIMENSIONS

LGH-100RX5-E

