

Air Conditioning

Product Information

LGH-200RX5-E : LOSSNAY

Commercial Series



This commercially orientated system can be utilised virtually anywhere to extract stale air and then recover the heating or cooling energy to either warm or cool incoming fresh air.

FEATURES



Airflow (m ³ /h) - Lo-Hi-ExHi	1580-2000-2000
External Static Pressure (Pa) - Lo-Hi-ExHi	65-105-165
Sound Pressure Level (dBA) Lossnay Ventilation - Lo-Hi-ExHi	34-38-40
Sound Pressure Level (dBA) Bypass Ventilation - Lo-Hi-ExHi	35-39-41
Electrical Supply	220-240V, 50HZ
Fuse rating (BS88) - HRC (A)	16
Starting Current (A)	11.9
Running Current (A) - Lo-Hi-ExHi	3.40-4.20-4.80
Power Input (W) - Lo-Hi-ExHi	785-980-1100
Temperature Exchange Efficiency (%) - Lo-Hi-ExHi	83-80-80
Enthalpy Exchange Efficiency Heating (%) - Lo-Hi-ExHi	73.5-?-?
Enthalpy Exchange Efficiency Cooling (%) - Lo-Hi-ExHi	72-71-?
Dimensions (mm) - W-D-H	1231-1144-798
Weight (kg)	118
Duct Size (mm)	(SA,RA)250 (OA,EA)270X700

DIMENSIONS

LGH-200RX5-E

