

Air Conditioning

Product Information

LGH-50RX5-E : LOSSNAY

Commercial Series



This commercially orientated system can be utilised virtually anywhere to extract stale air and then recover the heating or cooling energy to either warm or cool incoming fresh air.

FEATURES



LOSSNAY

Airflow (m ³ /h) - ExLo-Lo-Hi-ExHi	180-390-500-500
External Static Pressure (Pa) - ExLo-Lo-Hi-ExHi	10-60-90-155
Sound Pressure Level (dBA) Lossnay Ventilation - ExLo-Lo-Hi-ExHi	19-28-32-34
Sound Pressure Level (dBA) Bypass Ventilation - ExLo-Lo-Hi-ExHi	19-29-32.5-35
Electrical Supply	220-240V, 50HZ
Fuse Rating (BS88) - HRC (A)	6
Starting Current (A)	3.0
Running Current (A) - ExLo-Lo-Hi-ExHi	0.40-0.85-1.00-1.25
Power Input (W) - ExLo-Lo-Hi-ExHi	95-190-228-286
Temperature Exchange Efficiency (%) - ExLo-Lo-Hi-ExHi	86-81-78-78
Enthalpy Exchange Efficiency Heating (%) - ExLo-Lo-Hi-ExHi	78-71-?-?
Enthalpy Exchange Efficiency Cooling (%) - ExLo-Lo-Hi-ExHi	77-68-66.5-?
Dimensions (mm) - W-D-H	1016-888-315
Weight (kg)	32
Duct Size (mm)	200

DIMENSIONS

LGH-50RX5-E

