

MSH-GA50VB

Heat Pump R410A Classic Wall Mounted System

Mitsubishi Electric's new range of high specification, flat panel wall mounted models make use of traditional fixed speed technology, whilst providing extremely good value for money, costing approximately 30% less than the inverter equivalent. These units have extremely quiet sound levels, whilst also delivering economical air conditioning, with improved COP/EER figures. Ideal for use in any size room, this unit comes equipped with a wide-angle airflow system, as well as an automatic swing vane, allowing airflow to be extended to every corner of a room.

Air Cleaning Filter is optional







Pictures not to scale

Product Details

MUH-GA50VB Outdoor Unit

Noise (dBA) (Heating /Cooling) - Lo-Mi-Hi

Fuse Rating (BS88) - HRC (A)

Power Input (kW) - Heating (UK)

Power Input (kW) - Cooling (UK)

Power Input (kW) - Heating (Nominal)

Power Input (kW) - Cooling (Nominal)

Running Current (A) - Heating / Cooling

Width - mm

Depth - mm

Height - mm

Weight - kg

Phase

Electrical Supply

Starting Current (A)

Mains Cable No. Cores

Max Height Difference (m)

Max Pipe Length (m)


Charge (kg) - 7m

MSH-GA50VB Indoor Unit	
Capacity (kW):	
Heating (Nominal)	5.2
Cooling (Nominal)	5.0
Heating (UK)	4.3
Cooling (UK)	4.95
SHF R410A (Nominal)	0.65
COP / EER (Nominal)	3.23 / 2.81
Energy Label Heating / Cooling	C / C
Width - mm	325
Depth - mm	258
Height - mm	1100
Weight - kg	16
Airflow (m3/min) (Heating /Cooling) - Lo-Mi-Hi	8.8-10.7-12.8 /8.8- 10.7-12.8
Noise (dBA) (Heating /Cooling) - Lo-Mi-Hi	34-38-42 /34-38-42
Pipe Size Gas mm (in)	12.7 (1/2)
Pipe Size Liquid mm (in)	6.35 (1/4)
Electrical Supply	Fed byoutdoor unit
Phase	Single
Fuse Rating (BS88) - HRC (A)	6
Power Input (kW) - Heating (Nominal)	0.06
Power Input (kW) - Cooling (Nominal)	0.06
Power Input (kW) - Heating (UK)	0.06
Power Input (kW) - Cooling (UK)	0.06
Running Current (A) - Heating / Cooling	0.3/0.3
Interconnecting Cable No. Cores	2


Dimensions

MSH-GA50VB


Upper View >











MUH-GA50VB

850

290

605

47

Single

16

1.55

1.72

1.405

1.364

7.23/7.93

37

3

25


10


1.8


34-38-42 /34-38-42

220-240v, 50Hz

Upper View >







MITSUBISHI AIR CONDITIONING SYSTEMS

Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.



Tel:

Fax: