# Air Conditioning

## **Product Information**

MSZ-FH35VE Inverter Heat Pump Wall Mounted System Making a World of Difference



The MSZ-FH series is our most energy efficient M Series wall mounted unit to date.

### **Key Features**

- Swing Vane Mode with Auto Vane Shutter
- Infra-red remote controller
- Econo Cool allows set temperature to be raised by 2°C without any loss of comfort and a 20% gain in energy efficiency
- Auto-Restart
- Quiet operation
- Auto-Changeover
- Hot Start draught prevention
- Plasma Quad filter system
- Quick clean design
- Replace Technology available
- I-See Sensor
- Electro anti-allergy filter



Air Conditioning | Heating Ventilation | Controls

### **Product Information**


# Air Conditioning

### MSZ-FH35VE Inverter Heat Pump Wall Mounted System

Making a World of Difference

MSZ-FH - INDOOR UNIT		MSZ-FH35VE
CAPACITY (kW)	Heating (nominal)	4.0 (1.0-6.3)
	Cooling (nominal)	3.5 (0.8-4.0)
	Heating (UK)	3.3 (0.8-5.2)
	Cooling (UK)	3.47 (0.79-3.97)
SHF (nominal & UK)		0.84
COP / EER (nominal)		5.00 / 4.27
SCOP / SEER (BS EN14825)		5.1 / 8.9
ErP ENERGY EFFICIENCY CLASS Heating/Cooling		A+++ / A+++
AIRFLOW (I/s) Heating - Silent-Lo-Mid-Hi-Shi		67-78-107-153-220
Cooling - Silent-Lo-Mid-Hi-Shi		65-78-105-143-193
PIPE SIZE mm (in)	Gas	9.52 (3/8")
	Liquid	6.35 (1/4")
SOUND PRESSURE LEVEL (dBA) Heating/Cooling - Silent-Lo-Mi-Hi-Shi		21-24-29-36-44 / 21-24-29-36-42
SOUND POWER LEVEL (dBA)		58
DIMENSIONS (mm)	Width x Depth x Height	925 x 234 x 305
WEIGHT (kg)		13.5
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) – HRC (A)		6
INTERCONNECTING CABLE No. CORES		4

### DIMENSIONS



MUZ-FH - OUTDOOR UNIT	MUZ-FH35VE
SOUND PRESSURE LEVEL (dBA) Heating/Cooling	50 / 49
SOUND POWER LEVEL (dBA) Cooling	61
WEIGHT (kg)	37
DIMENSIONS (mm) Width x Depth x Height	800 x 285 x 550
ELECTRICAL SUPPLY	220-240v, 50Hz
PHASE	Single
SYSTEM POWER INPUT (kW) Heating/Cooling (nominal)	0.800 / 0.820
Heating/Cooling (UK)	0.760 / 0.690
STARTING CURRENT (A)	3.9
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]	3.9 / 3.8 [9.6]
FUSE RATING (BS88) - HRC (A)	10
MAINS CABLE No. CORES	3
MAX PIPE LENGTH (m)	20
MAX HEIGHT DIFFERENCE (m)	12
CHARGE R410A (kg)	1.15







#### Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division

Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom – Japan – Thaliand – Malaysia. @Mitsubishi Electric Europe 2015. Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to nake any variation in technical specification to the equijment described, or to withdraw or reglace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on equest. Third-party product and brand names may be taxiomarks or registred trademarks of their respective owners.



Mitsubishi Electric UK's commitment to the environment



mitsubishielectric2



Note: The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and side specific conditions. Misubish Electrics air conditioning and heat yoump systems contain fluorinated greenhouse gases N4100, N407C and R134a.