


## MXZ-5A100VA

Inverter Heat Pump R410A Multi-Split Unit



- Up to 5 indoor units of mixed capacities may be connected to a single outdoor unit
- Single outdoor unit for minimal noise and space impact
- Units may be added within the capacity of the system as requirements change
- Energy saving inverter controlled performance



Pictures not to scale




## **Product Details**

MXZ-5A100VA	
Capacity (kW):	
Heating (Nominal) (Low - High)	12.0 (3.4 - 14.0)
Cooling (Nominal) (Low - High)	10.0 (3.7 - 11.0)
Heating (UK) (Low - High)	9.95 (2.85 - 11.65)
Cooling (UK) (Low - High)	9.9 (3.65 - 10.9)
COP / EER (Nominal)	4.23 / 3.41
Energy Label Heating / Cooling	A/A
Maximum Number of Connectable Indoor Units	5
Width - mm	900
Depth - mm	320
Height - mm	900
Weight - kg	68
Airflow (m3/min) (Heating /Cooling)	59.3 /56.6
Noise (dBA) (Heating /Cooling) - Lo-Hi	46-54 /45-51
Electrical Supply	220-240v, 50Hz
Phase	Single
Fuse Rating (BS88) - HRC (A)	25
Interconnecting Cable No. Cores	4
Power Input (kW) - Heating (Nominal)	2.835
Power Input (kW) - Cooling (Nominal)	2.935
Power Input (kW) - Heating (UK)	2.58
Power Input (kW) - Cooling (UK)	2.35
Starting Current (A)	12.88
Running Current (A) - Heating / Cooling	12.45 / 12.88
Mains Cable No. Cores	3
Charge R410A (kg) - 40m	4

Piping Restrictions	
Total Pipe Length (m)	80
Max Pipe Length per Indoor Unit (m)	25
Indoor to Outdoor Height (m)	15

## **Dimensions**

MXZ-5A100VA





Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: http://www.mitsubishielectric.co.uk/aircon

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.





Tel: Fax: