# Air Conditioning

## **Product Information**

PEAD-RP140JAQ: Power Inverter Heat Pump

R410A Ceiling Concealed Ducted System





Our wide range of Power Inverters offer customers high seasonal efficiency, advanced control options and quiet operation, whilst providing greater flexibility and ease of installation.



#### **FEATURES**








































INDOOR	
Heating Capacity (kW) (nominal)	16.0 (5.7 - 18)
Cooling Capacity (kW) (nominal)	13.4 (6.2 - 15.3)
Heating Capacity (kW) (UK)	13.6 (4.85 - 15.3)
Cooling Capacity (kW) (UK)	12.9 (5.7 - 14.1)
SHF (nominal and UK)	0.84
COP / EER (nominal)	3.81 / 3.07
SCOP / SEER	3.6 / 4.3
Energy Efficiency Class - Heating / Cooling	N/A / N/A
Airflow (m³/min) Lo-Mi-Hi	32 - 39 - 46
Pipe Size Gas (mm [in])	15.88 (5/8")
Pipe Size Liquid (mm ([in])	9.52 (3/8")
External Static Pressure (Pa) Lo-Mi-Mi2-Mi3-Hi	35 - 50 - 70 - 100 - 150
Sound Pressure Level (dBA) Lo-Mi-Hi	34 - 38 - 43
Sound Power Level (dBA) Cooling	66
Dimensions (mm) Width x Depth x Height	1600 x 732 x 250
Weight (kg)	47
Electrical Supply	FED BY OUTDOOR UNIT
Phase	SINGLE
Fuse Rating (BS88) - HRC (A)	6
Interconnecting Cable No. Cores	4

Fuse Rating (BS88) - HRC (A)	6
Interconnecting Cable No. Cores	4
OUTDOOR	
Sound Pressure Level (dBA) Heating / Cooling	52 / 50
Sound Power Level (dBA) Cooling	70
Weight (kg)	119
Dimensions (mm) Width x Depth x Height	1050 x (330+30) x 1338
Electrical Supply	220-240V, 50HZ
Phase	SINGLE
System Power Input (kW) - Heating / Cooling (nominal)	4.20 / 4.36
System Power Input (kW) - Heating / Cooling (UK)	3.88 / 3.57
Starting Current (A)	12
System Running Current (A) [MAX] - Heating / Cooling	22.69 / 21.28 [30.8]
Fuse Rating (BS88) - HRC (A)	40
Mains Cable No. Cores	3
Max Pipe Length (m)	75
Max Height Difference (m)	30
Charge R410A (kg) - Pre charged length (m)	5 - 30


### **DIMENSIONS**

PEAD-RP140JAQ



#### **DIMENSIONS**

PUHZ-ZRP140VKA





 $\epsilon$