Air Conditioning

Product Information

PEAD-RP Standard Inverter Heat Pump Ceiling Concealed Ducted System (Three Phase) Making a World of Difference



PEAD-RP Standard Inverter Heat Pump

Ceiling Concealed Ducted System (Three Phase)

Our Standard Inverter range offers customers all the features and benefits of inverter technology whilst being cost effective.



Air Conditioning | Heating Ventilation | Controls

Key Features

- Auto-Restart
- Quiet operation
- Auto-Changeover
- Hot Start draught prevention
- Factory charged refrigerant up to 30m
- Long-life filter
- Low unit height entire range only 250mm
 minimal intrusion into occupied space
- Drain lift pump as standard
- High external static pressure
- Replace Technology available
- Refrigerant volume check function
- Duty Standby Operation
- Noise Reduction
- Demand Control
- Optional Heating Only

Product Information

Air Conditioning

PEAD-RP Standard Inverter Heat Pump Ceiling Concealed Ducted System (Three Phase) Making a World of Difference



PEAD-RP - INDOOR UNITS		PEAD-RP100JAQ	PEAD-RP125JAQ	PEAD-RP140JAQ
CAPACITY (kW)	Heating (nominal)	11.2 (4.5-12.5)	14.0 (5.0-16.0)	16.0 (5.0-18.0)
	Cooling (nominal)	9.4 (4.9-11.2)	12.3 (5.5-14.0)	13.6 (5.5-15.0)
	Heating (UK)	9.5 (3.85-10.65)	11.9 (4.25-13.6)	13.6 (4.25-15.3)
	Cooling (UK)	8.65 (4.5-10.3)	11.3 (5.05-12.9)	12.5 (5.05-13.8)
SHF (nominal & UK)		0.85	0.85	0.84
COP / EER (nominal)		3.61 / 3.01	3.62 / 2.91	3.61 / 3.01
SCOP / SEER (BS EN14825)		3.8 / 4.6	3.9 / 3.5	3.7 / 3.2
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A/B	N/A	N/A
AIRFLOW (m ³ /min)	Lo-Mi-Hi	24-29-34	29.5-35.5-42	32-39-46
PIPE SIZE mm (in)	Gas	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")
	Liquid	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")
EXTERNAL STATIC PRESSURE (Pa)		35-50-70-100-150	35-50-70-100-150	35-50-70-100-150
SOUND PRESSURE LEVEL (dBA) Lo-Mi-Hi		29-34-38	33-36-40	34-38-43
SOUND POWER LEVEL (dBA)		61	63	66
DIMENSIONS (mm)	Width x Depth x Height	1400 x 732 x 250	1400 x 732 x 250	1600 x 732 x 250
WEIGHT (kg)		41	43	47
ELECTRICAL SUPPLY		Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6	6	6
INTERCONNECTING CABLE No. Cores		4	4	4

PUHZ-P - OUTDOOR UNITS	PUHZ-P100YHA2 3 Three Phase	PUHZ-P125YHA ③ Three Phase	PUHZ-P140YHA ③ Three Phase
SOUND PRESSURE LEVEL (dBA) Heating/Cooling	54 / 50	55 / 51	56 / 52
SOUND POWER LEVEL (dBA) Cooling	70	71	73
WEIGHT (kg)	77	101	101
DIMENSIONS (mm) Width x Depth x Height	950 x 330 + 30 x 943	950 x 330 + 30 x 1350	950 x 330 + 30 x 1350
ELECTRICAL SUPPLY	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz
PHASE	Three	Three	Three
SYSTEM POWER Heating/Cooling (nominal)	3.103 / 3.120	3.870 / 4.220	4.430 / 4.520
INPUT (kW) Heating/Cooling (UK)	2.76 / 2.65	3.44 / 3.59	3.94 / 3.84
STARTING CURRENT (A)	4.0	5.0	5.0
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]	6.83 / 6.68 [15.65]	8.38 / 8.58 [15.76]	10.07 / 10.52 [15.78]
FUSE RATING (BS88) - HRC (A)	16	16	16
MAINS CABLE No. Cores	5	5	5
MAX PIPE LENGTH (m)	50	50	50
MAX HEIGHT DIFFERENCE (m)	30	30	30
CHARGE R410A (kg)	3.0	4.5	4.5

3 Three Phase



Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division

Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland

Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom – Japan – Thaland – Malaysia. (Mitsubish) Electric Europe 2014. Mitsubish) Electric are trademarks of Mitsubish Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withorulaw or replace products without promotilication or public amouncement. Mitsubish Electric's constantly developing and improving its product. All descriptions, librations, drawings and specifications in this publication present only general particulars and shall for more any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registred trademarks of their respective owners.





Mitsubishi Electric UK's commitment to the environment



in . Connect with Green Gateway

