Air Conditioning

Product Information

PEAD-RP140JAQ (Single Phase)
Power Inverter Heat Pump
Ceiling Concealed Ducted System

Making a World of Difference



Our wide range of Power Inverters offer customers high seasonal efficiency, advanced control options and quiet operation, whilst providing greater flexibility and ease of installation.

Key Features

- Reduced height entire range only 250mm
- Wider range of external static pressure settings across entire range
- Drain pump included as standard





Air Conditioning | Heating Ventilation | Controls



Product Information

DIMENSIONS

PEAD-RP140JAQ (Single Phase)
Power Inverter Heat Pump
Ceiling Concealed Ducted System

Making a World of Difference


Air Conditioning

PEAD-RP - INDOOR UNITS		PEAD-RP140JAQ	
CAPACITY (kW)	Heating (nominal)	16.0 (5.7-18.0)	
	Cooling (nominal)	13.4 (6.2-15.3)	
	Heating (UK)	13.6 (4.85-15.3)	
	Cooling (UK)	12.9 (5.7-14.1)	
SHF (nominal & UK)		0.84	
COP / EER (nominal)		3.93 / 3.10	
SCOP / SEER (BS EN14825)		4.0 / 4.8	
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	N/A	
AIRFLOW (I/s)	Lo-Mi-Hi	533-650-767	
PIPE SIZE mm (in)	Gas	15.88 (5/8")	
	Liquid	9.52 (3/8")	
EXTERNAL STATIC PRESSURE (Pa)		35-50-70-100-150	
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Mi2-Mi3-Hi	34-38-43	
SOUND POWER LEVEL (dBA)		66	
DIMENSIONS (mm)	Width x Depth x Height	1600 x 732 x 250	
WEIGHT (kg)		47	
ELECTRICAL SUPPLY		Fed by Outdoor Unit	
FUSE RATING (BS88) - HRC (A)		6	
INTERCONNECTING CABLE No. Cores		4	

PUHZ-ZRP - OUTDOOR UNITS		PUHZ-ZRP140VKA2
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		52 / 50
SOUND POWER LEVEL (dBA) Heating/Cooling		70
WEIGHT (kg)		118
DIMENSIONS (mm)	Width x Depth x Height	1050 x 330 + 40 x 1338
ELECTRICAL SUPPLY		220-240v, 50Hz
PHASE		Single
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	3.81 / 4.36
	Heating/Cooling (UK)	3.04 / 3.74
STARTING CURRENT (A)		12.0
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		20.75 / 19.25 [30.8]
FUSE RATING (BS88) - HRC (A)		40
MAINS CABLE No. Cores		3
MAX PIPE LENGTH (m)		75
MAX HEIGHT DIFFERENCE (m)		30
CHARGE R410A (kg) - 30m		5.0



Front View Upper View Suspension bolt hole 4-14x30 Slot 4-14x30 Slot



Side View

 Model
 A
 B
 C
 D
 E
 F

 PEAD-RP140JAQ 1600
 1654
 1700
 1560
 16
 1500



Telephone: 01707 282880

 $email: air.conditioning@meuk.mee.com \\ web: www.airconditioning.mitsubishielectric.co.uk$

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)


Country of origin: United Kingdom — Japan — Thalland — Malaysia. (Mitsubishi Electric Europe 2015. Mitsubish and Mitsubish Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification for the equipment described, or to withdraw or replace products without prior notification or public amountament. Missubishi Electric is constantly developing and improving its products. All descriptions, librations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sala, a copy of which is availation or nequest. Third-party product and branch anness may be trademarked or registered trademarks of their respective owners.













Mitsubishi Electric UK's commitment to the environment





