Air Conditioning

Product Information

PEAD-RP60JAQ (Single Phase)
Standard Inverter Heat Pump
Ceiling Concealed Ducted System

Making a World of Difference



Our Standard Inverter range offers customers all the features and benefits of inverter technology whilst being cost effective.

Key Features

- Reduced height entire range only 250mm
- Wider range of external static pressure settings across entire range
- Drain pump included as standard



Air Conditioning | Heating Ventilation | Controls



Product Information

PEAD-RP60JAQ (Single Phase) **Standard Inverter Heat Pump** Ceiling Concealed Ducted System

Making a World of Difference


Air Conditioning


PEAD-RP - INDOOR UNITS		PEAD-RP60JAQ
CAPACITY (kW)	Heating (nominal)	7.0 (2.5-8.0)
	Cooling (nominal)	5.7 (2.3-6.3)
	Heating (UK)	5.95 (2.13-6.80)
	Cooling (UK)	5.24 (2.12-5.80)
SHF (nominal & UK)		0.86
COP / EER (nominal)		3.63 / 3.41
SCOP / SEER (BS EN14825)		4.0 / 5.6
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A+ / A+
AIRFLOW (I/s)	Lo-Mi-Hi	242-300-350
PIPE SIZE mm (in)	Gas	15.88 (5/8")
	Liquid	6.35 (1/4")
EXTERNAL STATIC PRESSURE (Pa)		35-50-70-100-150
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Mi2-Mi3-Hi	25-29-33
SOUND POWER LEVEL (dBA)		55
DIMENSIONS (mm)	Width x Depth x Height	1100 x 732 x 250
WEIGHT (kg)		33
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. Cores		4

SUZ-KA - OUTDOOR UNITS		SUZ-KA60VA4
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		55 / 55
SOUND POWER LEVEL (dBA) Heating/Cooling		65
WEIGHT (kg)		50
DIMENSIONS (mm)	Width x Depth x Height	840 x 330 x 880
ELECTRICAL SUPPLY		220-240v, 50Hz
PHASE		Single
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	1.93 / 1.67
	Heating/Cooling (UK)	1.72 / 1.42
STARTING CURRENT (A)		8.6
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		7.50 / 8.60 [15.6]
FUSE RATING (BS88) - HRC (A)		20
MAINS CABLE No. Cores		3
MAX PIPE LENGTH (m)		30
MAX HEIGHT DIFFERENCE (m)		30
CHARGE R410A (kg)		1.80

Notes: All units charged to 7m (35-71), 30m (100-140) pipe length.







PEAD-RP60JAQ 1100 1154 1200 1060 11 1000





Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)


rogin: United Angloom – Japan – Inlaeria – Mealysa, . Givitsubaris becthic Europe 2015. Missubsit and Missubsit becthic are trademarks of Missubsit becthic Europe 101. The company reserves make any variation in technical specification to the equipment described, or to whiteheav or replace products without prior notification or public announcement. Missibist Bectric is consistantly developing viving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to any Semeral Conditions of Sela, a copy of which is a salidate) on request. Third-party product and be brand marker only be trademarks or registered trademarks of their respective owners.













Mitsubishi Electric UK's commitment to the environment





