# Air Conditioning

# **Product Information**

**PKA-RP35HAL** (Single Phase) **Power Inverter Heat Pump** Wall Mounted System

Making a World of Difference

mr.slim.



Our wide range of Power Inverters offer customers high seasonal efficiency, advanced control options and quiet operation, whilst providing greater flexibility and ease of installation.

## **Key Features**

- Flat panel, compact indoor unit design
- Adjustable louvres for uniform air distribution
- Internal pipe connection to wall mounted unit for easy and neat installation





Air Conditioning | Heating Ventilation | Controls



# **Product Information**


**PKA-RP35HAL** (Single phase) **Power Inverter Heat Pump** Wall Mounted System

## Making a World of Difference


PKA-RP - INDOOR UNITS		PKA-RP35HAL
CAPACITY (kW)	Heating (nominal)	4.1 (1.6-5.2)
	Cooling (nominal)	3.6 (1.6-4.5)
	Heating (UK)	3.5 (1.35-4.4)
	Cooling (UK)	3.3 (1.45-4.15)
SHF (nominal & UK)		0.81
COP / EER (nominal)		3.83 / 3.83
SCOP / SEER (BS EN14825)		3.9 / 5.7
ErP ENERGY EFFICIENCY CLASS Heating/Cooling		A / A+
AIRFLOW (I/s)	Lo-Mi-Hi	150-175-200
PIPE SIZE mm (in)	Gas	12.7 (1/2")
	Liquid	6.35 (1/4")
SOUND PRESSURE LEVEL (dBA)		36-40-43
SOUND POWER LEVEL (dBA)		60
DIMENSIONS (mm)	Width x Depth x Height	898 x 249 x 295
WEIGHT (kg)		13
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. Cores		4

Air Conditioning

PUHZ-ZRP -	OUTDOOR UNITS	PUHZ-ZRP35VKA
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		46 / 44
SOUND POWER LEVEL (dBA) Cooling		65
WEIGHT (kg)		43
DIMENSIONS (mm)	Width x Depth x Height	809 x 300 x 630
ELECTRICAL SUPPLY		220-240v, 50Hz
PHASE		Single
SYSTEM POWER	Heating/Cooling (nominal)	1.07 / 0.94
INPUT (kW)	Heating/Cooling (UK)	0.84 / 0.91
STARTING CURRENT (A)		4.0
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		4.22 / 3.94 [13.4]
FUSE RATING (BS88) - HRC (A)		16
MAINS CABLE No. Cores		3
MAX PIPE LENGTH (m)		50
MAX HEIGHT DIFFERENCE (m)		30
CHARGE R410A (kg) - 30m		2.2



### Front View



#### Side View





MITSUBISHI ELECTRIC Changes for the Better

#### Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division

Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom – Japan – Thaland – Melaysia. @Mitsubishi Electric Europe 2015. Mitsubishi Blectric are trademarks of Mitsubishi Electric Europe R.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public amouncement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication resent only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a cooy of which is available on request. Third-party noduct and brand remes may be trademarks or freigheed trademarks of the respective owners.



Mitsubishi Electric UK's commitment to the environment



You mitsubishielectric2



Note: The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electriciar/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Misubikit Becritics air conditioning and heat pump systems contain fluorinated greenhouse gases R410A, R407C and R134a.