

Air Conditioning

Product Information

PKA-RP100KAL (Single Phase)
Zubadan Inverter Heat Pump
Wall Mounted System

Making a
World of
Difference

Mr.SLIM™



The Mr Slim Zubadan Inverter heat pumps achieve an excellent heating performance even when the outdoor air temperature is as low as -25°C .

ZUBADAN

Key Features

- Flat panel, compact indoor unit design
- Stable heating performance - Full heating capacity at -15°C , a 30% capacity improvement over the next size up Power Inverter
- Expanded heating operation - Will work effectively even when the outdoor ambient air temperature is -25°C
- Stable operation - Utilising the flash injection circuit, the Zubadan models have reduced defrost times and can provide continuous heating for up to 150 mins
- Quick start-up - At -20°C , max heating capacity is achieved in about 20 mins, improving comfort levels



Air Conditioning | Heating
Ventilation | Controls

Air Conditioning


Product Information

PKA-RP100KAL (Single Phase)
Zubadan Inverter Heat Pump
 Wall Mounted System


Making a
 World of
 Difference

PKA-RP - INDOOR UNITS		PKA-RP100KAL
CAPACITY (kW)	Heating (nominal)	11.2 (4.5-14.0)
	Cooling (nominal)	10.0 (4.9-11.4)
	Heating (UK)	11.1 (4.45-13.85)
	Cooling (UK)	9.2 (4.5-10.5)
SHF (nominal & UK)		0.73
COP / EER (nominal)		3.61 / 3.42
SCOP / SEER		3.8 / 5.2
E.P ENERGY EFFICIENCY CLASS Heating/Cooling		A / A
AIRFLOW (l/s)	Lo-Mi-Hi	333-383-433
PIPE SIZE mm (in)	Gas	15.88 (5/8")
	Liquid	9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Hi	41-45-49
SOUND POWER LEVEL (dBA)		65
DIMENSIONS (mm) Width x Depth x Height		1170 x 295 x 365
WEIGHT (kg)		21
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. Cores		4


DIMENSIONS



PUHZ-SHW - OUTDOOR UNITS		PUHZ-SHW112VHA
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		52 / 51
SOUND POWER LEVEL (dBA) Heating/Cooling		69
WEIGHT (kg)		120
DIMENSIONS (mm) Width x Depth x Height		950 x 330 + 30 x 1350
ELECTRICAL SUPPLY		220-240v, 50Hz
PHASE		Single
SYSTEM POWER Heating/Cooling (nominal)		3.10 / 2.92
INPUT (kW) Heating/Cooling (UK)		2.76 / 2.49
STARTING CURRENT (A)		14
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		11.78 / 11.67 [35.6]
FUSE RATING (BS88) - HRC (A)		40
MAINS CABLE No. Cores		3
MAX PIPE LENGTH (m)		75
MAX HEIGHT DIFFERENCE (m)		30
CHARGE R410A (kg) - 30m		5.5



Side View



Telephone: 01707 282880

email: www.airconditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
 Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland
 Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom - Japan - Thailand - Malaysia. ©Mitsubishi Electric Europe 2015. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.



Note: The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Mitsubishi Electric's air conditioning and heat pump systems contain fluorinated greenhouse gases R410A, R407C and R134a.



www.greengateway.mitsubishielectric.co.uk
 Mitsubishi Electric UK's commitment
 to the environment

Follow us @meuk_Jes
 Follow us @green_gateway

Mitsubishi Electric
 Living Environmental Systems UK

YouTube
 mitsubishielectric2

Effective as of April 2015