



PLA-RP60BA

Power Inverter Heat Pump

R410A 4-Way Blow Ceiling Cassette System

Advanced inverter technology makes the Mr Slim Power Inverter the number one choice for improving comfort. They provide energy savings of up to 70% annually when compared to a previous non-inverter model. Operating noise has also been reduced thanks to improvements in fan design, while existing pipe work is reusable for easier maintenance and installation.

- **Airflow controllable for ceiling heights up to 4.2m, with automatic adjustment of fan speed**
- **Reduced draft air distribution, with independent vane control**
- **Filter lowering operation down to 4m (optional PLP-6BAJ grille required)**
- **Optional 'I See Sensor' for energy saving and smooth temperature control throughout the room**



Pictures not to scale

Product Details

PLA-RP60BA Indoor Unit

Capacity (kW):	
Heating (Nominal) (Low - High)	7.00 (2.80 - 8.20)
Cooling (Nominal) (Low - High)	6.00 (2.70 - 6.70)
Heating (UK) (Low - High)	5.95 (2.40 - 6.95)
Cooling (UK) (Low - High)	5.40 (2.45 - 6.05)
SHF R410A (Nominal)	0.76
COP / EER (Nominal)	3.78 / 3.64
Energy Label Heating / Cooling	A / A
Width (grille) - mm	840 (950)
Depth (grille) - mm	840 (950)
Height (grille) - mm	258 (35)
Weight (grille) - kg	23 (6)
Airflow (m3/min) - Lo-Mi1-Mi2-Hi	12-14-16-18
Noise (dBA) - Lo-Mi1-Mi2-Hi	28-29-31-32
Pipe Size Gas mm (in)	9.52 (3/8)
Pipe Size Liquid mm (in)	15.88 (5/8)
Electrical Supply	Fed by Outdoor Unit
Phase	Single
Fuse Rating (BS88) - HRC (A)	6
Interconnecting Cable No. Cores	4
Remote Controller Ref	PAR-21MAA


PUHZ-RP60VHA3 Outdoor Unit

Width - mm	950
Depth - mm	330 + 30
Height - mm	943
Weight - kg	68
Noise (dBA) (Heating /Cooling)	48 /47
Electrical Supply	220-240v, 50Hz
Phase	Single
Fuse Rating (BS88) - HRC (A)	25
SystemPower Input (kW) - Heating (Nominal)	1.85
SystemPower Input (kW) - Cooling (Nominal)	1.65
SystemPower Input (kW) - Heating (UK)	1.65
SystemPower Input (kW) - Cooling (UK)	1.4
SystemRunning Current (A) - Heating / Cooling	8.29 / 7.4
Mains Cable No. Cores	3
Max Pipe Length (m)	50
Max Height Difference (m)	30
Charge (kg) - 30m	3.5


Dimensions

PLA-RP60BA


Upper View >



Front View >




Side View >




PUHZ-RP60VHA3


Upper View >



Front View >



Side View >



Telephone: 01707 282880

Email: air.conditioning@meuk.mee.com Website: <http://www.mitsubishielectric.co.uk/aircon>

Tel:
Fax:

Mitsubishi Electric reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement.

