

Air Conditioning

Product Information

PLA-RP125BA : Standard Inverter Heat Pump


R410A 4-Way Blow Ceiling Cassette System



Our standard inverter range offers customers all the features and benefits of inverter technology whilst being cost effective.



FEATURES



INDOOR

Heating Capacity (kW) (nominal)	14.0 (5 - 16)
Cooling Capacity (kW) (nominal)	12.3 (5.5 - 14)
Heating Capacity (kW) (UK)	11.9 (4.25 - 13.6)
Cooling Capacity (kW) (UK)	11.3 (5.05 - 12.9)
SHF (nominal and UK)	0.71
COP / EER (nominal)	3.41 / 3.01
SCOP / SEER	3.7 / 3.6
Energy Efficiency Class - Heating / Cooling	N/A / N/A
Pipe Size Gas (mm [in])	15.88 (5/8")
Pipe Size Liquid (mm [in])	9.52 (3/8")
Airflow (m³/min) Lo-Mi-Mi2-Hi	22 - 25 - 28 - 31
Sound Pressure Level (dBA) Lo-Mi-Mi2-Hi	34 - 36 - 39 - 41
Sound Power Level (dBA) Cooling	63

Dimensions (mm) Width x Depth x Height	840(950) x 840(950) x 298(35)
Weight (kg) Unit / grille	25 / 6
Electrical Supply	FED BY OUTDOOR UNIT
Phase	SINGLE
Fuse Rating (BS88) - HRC (A)	6
Interconnecting Cable No. Cores	4


OUTDOOR

Sound Pressure Level (dBA) Heating / Cooling	55 / 51
Sound Power Level (dBA) Cooling	71
Weight (kg)	99
Dimensions (mm) Width x Depth x Height	950 x (330+30) x 1350
Electrical Supply	220-240V, 50HZ
Phase	SINGLE
System Power Input (kW) - Heating / Cooling (nominal)	4.11 / 4.09
System Power Input (kW) - Heating / Cooling (UK)	3.66 / 3.48
Starting Current (A)	15
System Running Current (A) [MAX] - Heating / Cooling	17.68 / 18.37 [29.0]
Fuse Rating (BS88) - HRC (A)	32
Mains Cable No. Cores	3
Max Pipe Length (m)	50
Max Height Difference (m)	30
Charge R410A (kg) - Pre charged length (m)	4.5 - 30


DIMENSIONS

PLA-RP125BA


Upper View >



Front View >




Side View >



DIMENSIONS


PUHZ-P125VHA3

Upper View >



	A
PUHZ-P125/140VHA3	1076
PUHZ-P125/140YHA	994

Front View >



Side View >

