

Air Conditioning

Product Information

PLA-RP71BA : Standard Inverter Heat Pump

R410A 4-Way Blow Ceiling Cassette System

Mr.SLIM™



Our standard inverter range offers customers all the features and benefits of inverter technology whilst being cost effective.



FEATURES



INDOOR

Heating Capacity (kW) (nominal)	8.0 (2.6 - 10.2)
Cooling Capacity (kW) (nominal)	7.1 (2.8 - 8.1)
Heating Capacity (kW) (UK)	7.4 (2.21 - 8.67)
Cooling Capacity (kW) (UK)	6.53 (2.57 - 7.45)
SHF (nominal and UK)	0.73
COP / EER (nominal)	3.56 / 3.38
SCOP / SEER	4.3 / 5.8
Energy Efficiency Class - Heating / Cooling	A+ / A+
Pipe Size Gas (mm [in])	15.88 (5/8")
Pipe Size Liquid (mm [in])	9.52 (3/8")
Airflow (m³/min) Lo-Mi-Mi2-Hi	14 - 16 - 18 - 21
Sound Pressure Level (dBA) Lo-Mi-Mi2-Hi	28 - 30 - 32-34
Sound Power Level (dBA) Cooling	56
Dimensions (mm) Width x Depth x Height	840(950) x 840(950) x 258(35)
Weight (kg) Unit / grille	23 / 6
Electrical Supply	FED BY OUTDOOR UNIT
Phase	SINGLE
Fuse Rating (BS88) - HRC (A)	6
Interconnecting Cable No. Cores	4


OUTDOOR

Sound Pressure Level (dBA) Heating / Cooling	55 / 55
Sound Power Level (dBA) Cooling	69
Weight (kg)	53
Dimensions (mm) Width x Depth x Height	840 x 330 x 880
Electrical Supply	220-240V, 50HZ
Phase	SINGLE
System Power Input (kW) - Heating / Cooling (nominal)	2.24 / 2.10
System Power Input (kW) - Heating / Cooling (UK)	1.99 / 1.79
Starting Current (A)	9.29
System Running Current (A) [MAX] - Heating / Cooling	9.38 / 9.36 [16.6]
Fuse Rating (BS88) - HRC (A)	20
Mains Cable No. Cores	3
Max Pipe Length (m)	30
Max Height Difference (m)	30
Charge R410A (kg) - Pre charged length (m)	1.8 - 30


DIMENSIONS

PLA-RP71BA


Upper View >



Front View >



Side View >



DIMENSIONS

SUZ-KA71VA4

